



ATF MULTI, Synthetic Transmission fluid

Product code s3369, March, 2018
(supersedes all previous references)

Description

Synforce ATF MULTI is a full synthetic multifunctional Automatic Transmission Fluid for use in a wide range of vehicles.

Synforce ATF MULTI is specially formulated to conform to A WIDE RANGE OF SPECIFICATIONS and is suitable for use where these specifications are called for.

Allison C-4	Allison TES-295	Allison TES-389
Audi G 052 025-A2	Audi G 052 162-A1	BMW LA2634
BMW LT71141	Chrysler ATF's	Dexron®
Dexron® II	Dexron® IID	Dexron® III G
Dexron® III H	Dexron® VI	Esso LT 71141
Ford MERCON® V	Ford MERCON® LV	Ford MERCON® SP
Ford MERCON®	LV Honda ATF-ZI	Hyundai SP-II
Hyundai SP-III	Idemitsu K17	JASO 1A
JWS 3309	Kia SP-II	Kia SP-III
MAN 339F	MAN 339 V1	MAN 339 V2
MAN 339 Z1	MAN 339 Z2	MAN 339 Z3
Mazda ATF-III	Mazda ATF-MV	BTR 85LE & 95LE
MB 236.1/ 236.2/ 236.5/ 236.6/ 236.7/ 236.9/ 236.10/ 236.81	Mitsubishi Diamond SP-II	Mitsubishi Diamond SP-II
Mitsubishi Diamond SP-III	Nissan Matic-D	Nissan Matic-J
Nissan Matic-K	Shell LA2634	Subaru ATF
Texaco ETL-7045E	Texaco ETL-8072B	Texaco N402
Toyota T-III	Toyota T-IV+	Toyota T-IV
Voith 55.6335.XX (607)	Voith 55.6335.XX (G1363)	Volvo 97340
ZF TE-ML 03D	ZF TE-ML 04D	ZF TE-ML 09
ZF TE-ML 14A	ZF TE-ML 14B	ZF TE-ML 16L
ZF TE-ML 17C	ZF Lifeguard 3,4,5 speed	

Note: for ZF 6,7,8 & 9 speed transmissions use our ATF 6FE

Typical Properties

Viscosity, cst@ 100 deg C	7.3
Viscosity, cst @ 40 deg C	35
Flash Point deg C	200
Viscosity index	180
Pour Point	-44 deg C

